Roundcube

IMAP   .

hosts

```
127.0.0.1        localhost
127.0.1.1        Servername
```

Roundcube

```
$ mysql -u root -p     // mysql
```

```
CREATE DATABASE roundcubemail;
GRANT ALL PRIVILEGES ON roundcubemail.* TO username@localhost IDENTIFIED BY
'password';
```

username@localhost   (ex:info@obg.com), password
                . roundcube   database configuration[1]   .

Roundcube   /usr/share/roundcube   logs, temp   707

/usr/share/roundcube/installer/index.php

```
ini_set('error_reporting', E_ALL&~E_NOTICE);        //
ini_set('error_reporting', E_ALL&~(E_NOTICE|E_STRICT));      //
```

     [round URL]/installer

- username_domain   !!
- default_host   obg.pe.kr
- imap_auth_type   PLAIN

- smtp_server   obg.pe.kr
-
- config.inc.php   <?php ?>   (?>   )
- {Roundcube   }/config
- config   707

.

- chmod 0600 /var/mail/*   (http://wiki2.dovecot.org/Errors/ChgrpNoPerm)

.

	mail.obg.co.kr
	vfinger
SSL	
	143

	mail.obg.co.kr
	vfinger
SSL	
	25

.

- http://jo.centis1504.net/?p=54
- http://trac.roundcube.net/wiki/Howto_Install
- http://wiki.qnap.com/wiki/RoundCube_Configuration
- http://forums.zpanelcp.com/archive/index.php/t-5667.html - SMTP

[1）

http://trac.roundcube.net/wiki/Howto_Install

From:
<http://obg.co.kr/doku/> - **OBG WiKi**

Permanent link:
http://obg.co.kr/doku/doku.php?id=linux:roundcube

Last update: **2020/11/29 14:09**